




Description: Headlight
Part Number: 121054-121146-121053-121216
Application: 1998-2002 Honda Accord



Tool needed: Flat head screw driver, 8mm socket, 10mm socket, wire splicer, electrical tape, scissors/knife

Step 1: Remove the two push pins located on the bumper by the inner headlight housing.



Step 2: Remove the 10mm screw holding the front bumper on both sides.

Step 3: Remove the screw from underneath the vehicle there will be a two at each end.

Step 4: Remove the 5 push pins from under the vehicle with the flat head screwdriver.



Step 5: Push the corner of the bumper down then pull away from the car do the same with the other side.

Step 6: Once both sides are loosened from the frame remove the front bumper.



Step 7: Use the 10mm socket to remove the one screw from the top of the headlight.

Step 8: Remove the one screw on the side of the headlight, this will be holding in the support frame.

Step 9: Remove the two 10mm from under the headlight support frame.



Step 10: Now remove the headlight from the frame.



Step 11: Twist off the Turn signals in the headlight.



Step 12: Twist off the headlight bulbs.




Step 13: Unclip the head light wire harness from the bulbs.



Now your headlight should be able to come right out.



Step 15: Use the scissors to expose the wires from the parking light.




Step 16: Splice the two red wires from the new headlight to the black and red wire to power the halos.





Step 17: Now use electrical tape to prevent any kind of power shortage.



Step 18: Plug in the wire harness into the new Anzo projector headlights.



Step 19: Plug in the wire harness into the new Anzo projector headlights.



Step 20: Twist in the turn signals into the new Anzo projector headlights.



Step 21: Screw in the headlights into the frame.



Step 22: Screw in one screw on the side and the two screws into the headlight support frame.



Step 23: Please check all functions to make sure they are in working order before driving.

AnzoUSA™ products are covered, by a limited one (1) year warranty, to be free of manufacturer's defects. However, certain AnzoUSA™ product categories have warranty policies which differ from this standard, please contact your representative for detailed category information. Damage due to improper installation or road hazards is not covered. Seller and manufacturers' only obligations shall be to replace the product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.